



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

2013FR "FREON" 503 Refrigerant
Revised 4-MAY-2004

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

"FREON" is a registered trademark of DuPont.

Corporate MSDS Number : DU001066
CAS Number : 50815-73-1
Formula : CHF₃/CClF₃ (AZEOTROPE)
Grade : REFRIGERANT

Company Identification

MANUFACTURER/DISTRIBUTOR
DuPont Fluoroproducts
1007 Market Street
Wilmington, DE 19898

PHONE NUMBERS

Product Information : 1-800-441-7515 (outside the U.S.
302-774-1000)
Transport Emergency : CHEMTREC 1-800-424-9300(outside U.S.
703-527-3887)
Medical Emergency : 1-800-441-3637 (outside the U.S.
302-774-1000)

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
"FREON" 503	50815-73-1	
METHANE, TRIFLUORO- ("FREON" 23)	75-46-7	40
*METHANE, CHLOROTRIFLUORO- ("FREON" 13)	75-72-9	60

* Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

HAZARDS IDENTIFICATION

Potential Health Effects

The material is untested for skin irritancy, is untested for eye irritancy, and is untested for animal sensitization.

Inhalation may include nonspecific discomfort, such as nausea, headache, or weakness; temporary nervous system depression with anaesthetic effects such as dizziness,

(HAZARDS IDENTIFICATION - Continued)

headache, confusion, incoordination, and loss of consciousness; or possibly with gross overexposure (> 20%), temporary alteration of the heart's electrical activity with irregular pulse, palpitations, or inadequate circulation. There are no reports of human sensitization. Individuals with preexisting diseases of the cardiovascular system may have increased susceptibility to the toxicity of excessive exposures.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, immediately remove to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with plenty of water. Treat for frostbite if necessary.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

Ingestion is not considered a potential route of exposure.

Notes to Physicians

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should only be used with special caution in situations of emergency life support.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : Will not burn
Flammable limits in Air, % by Volume
LEL : Not applicable
UEL : Not applicable
Autoignition : Not determined

(FIRE FIGHTING MEASURES - Continued)

Autodecomposition : >760 C (>1400 F)

Fire and Explosion Hazards:

Use water spray or fog to cool containers. Cylinders are equipped with temperature and pressure relief devices but may still rupture under fire conditions. Decomposition may occur.

Extinguishing Media

As appropriate for combustibles in area.

Fire Fighting Instructions

Self-contained breathing apparatus (SCBA) is required if cylinders rupture or release under fire conditions.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Accidental Release Measures

Ventilate area, especially low or enclosed places where heavy vapors might collect. Remove open flames. Self-contained breathing apparatus (SCBA) is required if a large spill or release occurs.

HANDLING AND STORAGE

Handling (Personnel)

Avoid breathing vapors or allowing liquid or cold vapors to contact skin and eyes. Use with sufficient ventilation to keep employee exposure below recommended limits.

Storage

Clean, dry area. Do not heat above 52 deg C (125 deg F).

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Normal ventilation for standard manufacturing procedures is generally adequate. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places.

Personal Protective Equipment

Butyl or neoprene gloves and chemical splash goggles should be used if contact is possible. Under normal manufacturing conditions, no respiratory protection is required when using this product. Self-contained breathing apparatus (SCBA) is required if a spill occurs.

Exposure Guidelines

Applicable Exposure Limits

METHANE, TRIFLUORO- ("FREON" 23)
PEL (OSHA) : None Established
TLV (ACGIH) : None Established
AEL * (DuPont) : 1000 ppm, 8 & 12 Hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Boiling Point : -88.8 C (-127.8 F)
Vapor Pressure : 566 psia at 15.6 deg C (60 deg F)
Vapor Density : 3.0 (Air = 1)
% Volatiles : 100 WT%
Evaporation Rate : >1 (CCl4 = 1)
Solubility in Water : 0.042 WT% @ 25 C (77 F)
pH : Neutral
Odor : Slight ethereal
Form : Gas
Color : Clear, colorless
Density : 1.233 g/cc at -30 deg C (-22 deg F) -
Liquid

STABILITY AND REACTIVITY

Chemical Stability

Material is stable. However, avoid open flames and high temperatures.

Incompatibility with Other Materials

Incompatible with alkali or alkaline earth metals- powdered Al, Zn, Be, etc.

Polymerization

Polymerization will not occur.

Other Hazards

Decomposition : "FREON" 503 Refrigerant can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides.

TOXICOLOGICAL INFORMATION

Animal Data

Anaesthetic effects, and nonspecific effects such as weight loss were observed at concentrations > 22% with FREON 23. No cardiac sensitization was observed in dogs after breathing 800,000 ppm of FREON 23 for periods of 5-10 minutes following an epinephrine challenge. Cardiac sensitization was observed in beagle dogs exposed to 800,000 ppm of FREON 13 for 5 minutes and challenged with adrenalin for 10 seconds.

No observed adverse effects were seen with FREON 13 at concentrations as high as 20% (v/v).

Tests in bacterial or mammalian cell cultures with FREON 23 demonstrate no mutagenic activity. Otherwise no animal test reports are available to define carcinogenic, mutagenic, embryotoxic, or reproductive hazards.

DISPOSAL CONSIDERATIONS

Waste Disposal

Comply with Federal, State, and local regulations. Remove to permitted waste disposal facility. Reclaim by distillation.

TRANSPORTATION INFORMATION

Shipping Information

DOT/IMO
Proper Shipping Name : CHLOROTRIFLUOROMETHANE AND
TRIFLUOROMETHANE AZEOTROPIC
MIXTURE
Hazard Class : 2.2
UN No. : 2599
DOT/IMO Label : NONFLAMMABLE GAS

Shipping Containers

Cylinders
Ton Tanks

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : Reported/Included.

TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

Acute : Yes
Chronic : No
Fire : No
Reactivity : No
Pressure : Yes

LISTS:

Extremely Hazardous Substance -No
CERCLA Hazardous Substance -No
Toxic Chemicals -(See Components Section)

OTHER INFORMATION

NFPA, NPCA-HMIS

NPCA-HMIS Rating
Health : 1
Flammability : 0
Reactivity : 1

Personal Protection rating to be supplied by user depending on use conditions.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS : MSDS Coordinator
> : DuPont Fluoroproducts
Address : Wilmington, DE 19898
Telephone : (800) 441-7515

Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS