



MSDS DETAIL

IDENTITY

MWH135 Wax Quickstick

Section I

Distributor's Name

South Bay Technology, Inc.

Emergency Telephone Number

(800) 724-7447

Address

1120 Via Callejon San Clemente, CA 92763

Telephone Number for information

(949) 492-2600

Date Prepared

04/05/02

Name of Preparer

Marne Andersen

Section II - Hazardous Ingredients/Identity Information

Hazardous Components	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Ethylene Glycol	C 50PPM	C 50PPM		29%
Phthalic Anhydride	1 PPM	1PPM		71%

Section III - Physical/Chemical Characteristics

Boiling Point

>212F

Specific Gravity (H2O = 1)

>1.0

Vapor Pressure (mm Hg.)

N/A

Melting point

N/A

Vapor Density (AIR = 1)

>1.0

Evaporation Rate (Butyl Acetate = 1)

N/A

Solubility in Water

Appearance and Odor

Clear solid, resin odor when heated

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

>160

Flammable Limits (LEL/UEL)

NAIF

Extinguishing Media

Foam, CO2, Dry powder

Special Fire Fighting Procedures

Do not use water

Unusual Fire and Explosion Hazards

NONE

Section V - Fire and Explosion Hazard Data

Stability

STABLE

Conditions to Avoid

Excessive heat, sparks, open flame

Incompatibility (Materials to Avoid)

NAIF

Hazardous Decomposition or Byproducts

Carbon Monoxide, Carbon Dioxide

Conditions to Avoid

Hazardous Polymerization

Will not occur

Section VI - Hazard Data

Eyes:	Inhalation?	Skin? See Physician.	Ingestion?
--------------	--------------------	--------------------------------	-------------------

Health Hazards (*Acute and Chronic*)

If heated to the melting point, the material may cause burns. Do not remove the material from 2nd or 3rd degree burns. Solvents may be used on minor burns.

Carcinogenicity:

Not listed as a carcinogen by IARC, NTP, or OSHA.

Signs and Symptoms of Exposure

Medical Conditions Generally Aggravated by Exposure

Emergency and First Aid Procedures

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Handling and Storing

Store in a cool, well ventilated area. Avoid excessive heat, sparks and flames. Do not take internally. Avoid prolonged breathing of vapor. Avoid prolonged contact with skin.

Waste Disposal Method

Comply with federal, state, local regulations.

Precautions to Be Taken Leaks or Spills

If material is unuseable, sweep up and dispose of in a metal container. Provide adequate ventilation. Avoid excessive heat, sparks and open flames.

Other Precautions

Section VIII - Control Measures

Respiratory Protection (*Specify Type*)

In confined areas or if material is pulverized, use nuisance mask.

Ventilation

Adequate ventilation to reduce levels of air contaminant below that which may cause personal injury or illness.

Protective Gloves

Rubber or neoprene gloves.

Eye Protection

Chemical splash goggles.

Other Protective Clothing or Equipment

Work/Hygienic Practices

Wash thoroughly after handling. Wash clothing before re-use.

NOTES