

Kurt J. Lesker Company
1515 Worthington Avenue
Clairton, PA 15025
www.lesker.com

MATERIAL SAFETY DATA SHEET

Trade Name: **TKO 77**

Date: August 3, 1998

CAS Number: See Below
Common name: Lubricating Oil
Commodity Code: 37-099

General Information: (412) 233-4200
Customer Service: (800) 245-1656
CHEMTREC Emergency: (800) 424-9300

MATERIAL HAZARD EVALUATION

(Per OSHA Hazard Communication Standard [29 CFR 1910.1200])

Health Precautions: Protect exposed skin from repeated or prolonged exposure.

Safety Precautions: This Material will burn when heated. Do not store material in open or unmarked containers.

HMS Code: (Health: 0) (Flammability: 1) (Reactivity: 0)

SECTION 1.0 -- GENERIC COMPOSITION / COMPONENTS

| <u>Component</u> | <u>CAS#</u> | <u>%</u> | <u>Hazard Data</u> |
|--------------------------|--|----------|---|
| Refined Petroleum Oil(s) | 64741-88-4 64742-01-4 64742-52-5 64742-62-7 | 100 | Oral LD ₅₀ (rat): >5g/kg Skin and Eye: Essentially non-irritating Inhalation LC ₅₀ /4H (rat): >5000mg/M ³ Hazard data are based upon similar components |

SECTION 2.0 -- PHYSICAL DATA

PHYSICAL HAZARD CLASSIFICATION (per 29 CFR 1910.1200)

| | | | | | |
|-----------------|----|-------------------|----|-------------|-----|
| Combustible: | No | Flammable: | No | Pyrophoric: | No |
| Compressed Gas: | No | Organic Peroxide: | No | Reactivity: | No |
| Explosive: | No | Oxidizer: | No | Stable: | Yes |

| | |
|---|-----------------------------------|
| Boiling Point, 760 mm Hg, °C (°F): | ~367-502 (~693 - 936) |
| Specific Gravity (60//60°F) (H ₂ O) = 1: | 0.88-0.91 |
| Vapor Density (Air = 1): | > 1 |
| % Volatiles by Volume: | Negligible |
| Melting Point, °C (°F): | NA |
| Vapor Pressure, mm Hg (25°C): | ~1.5 x 10 ⁻⁵ |
| Solubility in Water: | Negligible |
| Evaporation Rate (n-butyl acetate = 1): | < 1 |
| pH of Undiluted Product: | NA |
| Appearance and Odor: | Amber liquid, mild petroleum odor |

SECTION 3.0 -- FIRE AND EXPLOSION DATA

| | |
|--|--|
| Flash Point, OC, °C (°F): | 211 - 300 (412 - 570) |
| Flash Point, CC, °C (°F): | ND |
| Auto-ignition Temperature, °C (°F): | ND |
| NFPA Rating: | Health: <u>0</u> Flammability: <u>1</u> Reactivity: <u>0</u> |
| Flammable Limits (% by volume in air): | Lower: <u>ND</u> Upper: <u>ND</u> |
| Extinguishing Media: | CO ₂ , dry chemical, foam, water fog |
| Special Fire Fighting Procedure: | None |
| Unusual Fire or Explosion Hazard: | Water may cause frothing |

SECTION 4.0 -- REACTIVITY DATA

| | |
|---|--|
| Stability: | Stable. |
| Conditions Contributing to Instability: | None. |
| Incompatibility: | Strong oxidizers. |
| Hazardous Decomposition Products: (Thermal unless otherwise specified) | CO ₂ , CO under incomplete combustion. |
| Hazardous Polymerization: | Hazardous polymerization is not expected to occur. |

SECTION 5.0 -- SPILL, LEAK, AND DISPOSAL PROCEDURES

Procedure if Material is spilled:

- Remove sources of heat or ignition, provide ventilation, contain leak.
- **Small Spills:** Absorb released material with non-combustible absorbent. Place into containers for later disposal. (See Waste Disposal section below.)
- **Large Spills:** Evacuate area in the event of significant spills. Adequately ventilate area and determine potential exposure conditions. Exposure potential may require the use of respiratory protection. Use protective clothing. Contain spill in temporary dikes to avoid product migration and to assist in recovery. Do not allow material to escape into sewers, ground water, drainage ditches or surface waters.
- Control ignition sources around spill area. Use of a fire fighting foam blanket on spilled material will reduce vapor release and fire potential.
- Administer first aid as needed.
- Report spills as required to appropriate federal, state and local authorities.
- OSHA regulations may require establishing a regulated area with site control.

Waste Disposal:

- It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal.
- Transportation, treatment, storage and disposal of waste material must be in compliance with all regulatory requirements.
- Contact the RCRA/Superfund Hotline at (800) 424-9246 or your regional US EPA office for guidance concerning case specific disposal issues.

SECTION 5.0 -- SPILL, LEAK, AND DISPOSAL PROCEDURES (Cont.)

Protective Measures During Repair and Maintenance of Contaminated Equipment:

- Refer to Section 7.0 – Special Protection Information.
- Keep unnecessary persons from hazard area.
- Drain and purge equipment, as necessary, to remove material residues.
- Use gloves constructed of impervious materials such as neoprene or heavy nitrile and protective clothing if direct contact is anticipated.
- Provide ventilation to maintain exposure potential below applicable exposure levels.
- Eliminate heat and ignition sources.
- Remove contaminated clothing.
- Wash exposed skin thoroughly with soap and water.

SECTION 6.0 -- HEALTH HAZARD DATA

Health Hazard Classification (Per 29 CFR 1910.1200):

| | | | |
|---------------|----|-----------------------|----|
| HIGHLY TOXIC: | No | SENSITIZER: | No |
| TOXIC: | No | REPRODUCTIVE EFFECTS: | No |
| CORROSIVE: | No | MUTAGEN: | No |
| IRRITANT: | No | TARGET ORGAN: | No |

Carcinogen:

| <u>Product/Component</u> | <u>CAS No.</u> | <u>%</u> | <u>NTP</u> | <u>IARC</u> | <u>OSHA</u> | <u>Other</u> |
|--------------------------|----------------|----------|------------|-------------|-------------|--------------|
| TKO 77 | Mixture | 100 | No | No | No | No |

Toxicity Summary: Generally of a low order of toxicity.

Major Route of Entry: Inhalation of incidental mists, skin contact with liquids.

Acute Exposure Symptoms:

INHALATION: In enclosed spaces or when hot, vapors may reach concentrations sufficient to cause drowsiness, dizziness, headache, nausea, or lung irritation. Elevated mist concentrations well above applicable workplace levels can cause severe lung damage.

DERMAL: This material may cause mild transient skin irritation.

EYE: This material may cause mild transient eye irritation.

INGESTION: If swallowed, there is a risk of aspirating this material into the lungs. Aspirated Material can cause severe lung damage. Upon ingestion, slight gastrointestinal discomfort, diarrhea, and headache can occur.

INJECTION: Injection under the skin, in muscle or into the blood stream may cause irritation, inflammation, swelling or severe, permanent tissue damage. Most damage occurs during the first few hours.

SECTION 6.0 -- HEALTH HAZARD DATA (Cont.)

Chronic Exposure Symptoms:

Prolonged and/or frequent contact can cause drying, cracking (dermatitis) or folliculitis or skin irritation. Repeated or prolonged overexposure to oil mists can result in oil granuloma formation, respiratory tract irritation and an increased risk of infection.

Other Special Effects:

None Expected.

Medical Conditions Aggravated by Exposure:

None.

First Aid and Emergency Procedures for Acute Effect:

- Inhalation:** Move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, 100 percent humidified oxygen should be administered by a qualified individual. Seek medical attention immediately.
- Dermal:** Remove contaminated clothing. Wash exposed skin with soap and water. Launder clothing before use. Seek medical attention if tissue appears damaged or if irritation persists.
- Eyes:** Flush eyes with cool water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, irritation or pain persists.
- Ingestion:** Do not induce vomiting unless directed by a physician. Never give anything by mouth to a person who is not fully conscious. Seek medical attention immediately.
- Injection:** Injection under the skin, in muscle or into the blood stream is a medical emergency. Seek medical attention immediately.

Notes to Physicians:

The viscosity the product represented by this MSDS is greater than 400 SUS at 100°F. Upon ingestion, there is a low risk of aspiration into the lungs. Removal by gastric lavage should be considered. Subcutaneous or intramuscular injection requires prompt surgical debridement.

SECTION 7.0 – SPECIAL PROTECTION INFORMATION**Ventilation Requirements:**

Use in well-ventilated area. In confined space, mechanical ventilation may be required to keep levels of certain components below applicable workplace exposure levels as evaluated by designated and properly trained personnel.

SECTION 7.0 -- SPECIAL PROTECTION INFORMATION (Cont.)

Applicable Workplace Exposure Levels:

| Chemical Component | ACGIH TLV | ACGIH TLV | ACGIH | OSHA PEL | OSHA PEL | OSHA |
|----------------------|-------------------------|-------------------------|--------------------------------------|-----------|-------------------------|----------|
| | TWA | STEL/ Ceiling © Skin | TLV | TWA | STEL/ Skin | PEL |
| | ppm(mg/M ³) | ppm(mg/M ³) | ppm(mg/M ³) notation? | Ceiling © | ppm(mg/M ³) | notation |
| Oil Mist, Mineral | (5) | (10) | No | (5) | NE | No |

Specific Personal Protective Equipment:

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations.

Respirator: At elevated temperatures, vapor or mist concentrations may exceed applicable workplace exposure levels. Use a NIOSH or MSHA approved organic vapor/mist chemical cartridge when elevated airborne concentrations are anticipated.

Eyes: Use safety glasses. Use chemical splash goggles if splashing is anticipated.

Dermal: Use gloves constructed of impervious materials such as heavy nitrile rubber or neoprene if frequent or prolonged contact is expected.

Clothing or Equipment: Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder contaminated work clothes before reuse.

SECTION 8.0 -- TRANSPORTATION AND SPECIAL PRECAUTIONS

Storage: Store in a cool, dry, well ventilated area. Do not apply heat or flame to container. Keep separate from strong oxidizing agents.

Caution: Empty containers may contain product residues which could ignite with explosive force. Consult appropriate federal, state and local authorities before reusing, reconditioning, Reclaiming, recycling, or disposing of empty containers and/or waste residues of this product.

US Department of Transportation Information:

| | |
|------------------------------|----------------------------|
| PROPER SHIPPING NAME | Petroleum Lubricating Oils |
| HAZARD CLASS | Non-Hazardous |
| HAZARD IDENTIFICATION NUMBER | None Assigned |
| PACKAGING GROUP | None Assigned |
| PLACARD | None |
| COMPATIBILITY CATEGORY | Group 33 |
| CHRIS CODE | OLB |

SECTION 9.0 – ENVIRONMENTAL DATA

TITLE III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

Section 313 - Toxic Chemicals:

This product is not known to contain any components in concentrations above *de minimis* levels that are Listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 SARA.

Section 311/312 – Hazard Categories:

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below:

| | | | |
|----------------------------------|----|------------------------------------|----|
| Immediate (Acute) Health Hazard: | No | Sudden Release of Pressure Hazard: | No |
| Delayed (Chronic) Health Hazard: | No | Reactive hazard: | No |
| Fire Hazard: | No | | |

Section 302 – Extremely Hazardous Substances:

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous substances in 40 CFR 355 pursuant to the requirements of Section 302(a) of SARA.

Clean Water Act (CWA):

Under the CWA, discharges of crude oil and petroleum products to surface waters without federal and state permits must be reported immediately to the National Response Center at (800) 424-8802.

Comprehensive Environmental Response, Compensation, or Liability Act (CERCLA) Section 102 Hazardous Substances:

As defined by CERCLA, the term “hazardous substance” does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically listed or designated as a hazardous substance.

Toxic Substances Control Act (TSCA):

| <u>Reported in TSCA inventory as:</u> | <u>Product</u> | <u>Components</u> |
|---------------------------------------|----------------|-------------------|
| TKO 77 | | X |

SECTION 10 – LABELING

Note: This product has been determined not to be a physical or a health hazard as defined by the OSHA Hazard Communication Standard.

ALL STATEMENTS, INFORMATION, AND DATA PROVIDED IN THIS MATERIAL SAFETY DATA SHEET ARE BELIEVED TO BE ACCURATE AND RELIABLE , BUT ARE PRESENTED WITHOUT GUARANTEE, REPRESENTATION, WARRANTY, OR RESPONSIBILITY OF ANY KIND, EXPRESSED OR IMPLIED. ANY AND ALL REPRESENTAIONS AND/OR

WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY DISCLAIMED. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE. NOTHING CONTAINED HEREIN IS INTENDED AS PERMISSION, INDUCEMENT OR RECOMMENDATION TO VIOLATE ANY LAWS OR TO PRACTICE ANY INVENTION COVERED BY EXISTING PATENTS, COPYRIGHTS OR INVENTIONS.

END

Typical Properties:

ISO VG No.

68