



1254 Chestnut Street  
Newton, MA 02464-1418  
Tel: (617) 965-5511  
Fax: (617) 965-5818

## MATERIAL SAFETY DATA SHEET

PAGE 1  
12 December 2001

### SECTION 1. CHEMICAL IDENTIFICATION -----

----

CHEMICAL NAME: Organic Resin Solution  
TRADE NAME: SU-8 Series Resists  
PRODUCT #: See Table 1 – Section 9

### SECTION 2. COMPOSITION-----

-----

INGREDIENTS: Gamma Butyrolactone (CAS: 96-48-0); 22-60%  
Mixed Triarylsulfonium/ Hexafluoroantimonate Salt;  
(CAS: 89452-37-9)/(CAS: 71449-78-0) See Table 1, Section 9  
Propylene Carbonate (CAS: 108-32-7); 1-5%  
Epoxy Resin (CAS: 28906-96-9); 35-75%

### SECTION 3. HAZARD DATA-----

-----

INFLAMMABILITY: Combustible liquid.  
SKIN CONTACT: May cause skin irritation.  
EYE CONTACT: Severe eye irritant.  
INGESTION: May be harmful if swallowed in large quantities.  
INHALATION: May cause irritation..  
MUTAGENICITY: Not known to be mutagenic.  
CARCINOGENICITY: Not considered carcinogenic by NTP, IARC and OSHA  
TARGET ORGANS: Eyes, Epidermis.

### SECTION 4. FIRST AID MEASURES-----

-----

INHALATION: No occupational exposure limits have been developed for this material. Where exposure through inhalation may occur from use, NIOSH approved respiratory equipment is recommended.

INGESTION: If a large quantity swallowed, give lukewarm water. DO NOT induce vomiting. Risk of damage to lungs exceeds poisoning risk. Get medical attention immediately.

SKIN CONTACT: Rinse with water for 15 minutes while removing contaminated clothing and shoes. Wash affected area with soap and water. Wash contaminated clothing.

EYE CONTACT: Rinse immediately with water, flush for 15 min. lifting eyelids frequently. Get emergency medical assistance. Prompt action is essential.

CHEMICAL NAME: Organic Resin Solution  
TRADE NAME: SU-8 Resist Series

PRODUCT #: See Table 1 – Section 9

---

**SECTION 5. FIRE FIGHTING MEASURES**

---

**EXTINGUISHING**

**MEDIA:** Dry chemical, carbon dioxide, foam, water spray, and fog.

**SPECIAL FIRE FIGHTING**

**PRECAUTIONS:** Do not enter fire area without proper protection. Fight fire from a safe distance/protected location. Heat may build enough pressure to rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling. Avoid frothing, steam explosion. Burning liquid may float on water. Although water-soluble, may not be practical to extinguish fire by water dilution. Notify authorities immediately if liquid enters sewer, public waters.

**UNUSUAL FIRE OR**

**EXPLOSION HAZARDS:** Heat from fire can generate flammable vapor. When mixed with air and exposed to ignition source, vapors can burn in open or explode if confined. Vapors may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapor source. Fine sprays/mists may be combustible at temperatures below normal flash point.

**SECTION 6. ACCIDENTAL RELEASE PROCEDURES**

---

Evacuate Area.

Eliminate all ignition sources.

Wear self-contained breathing apparatus (SCBA), rubber boots, and heavy rubber gloves. Avoid eye or skin contact. Cover with dry absorbent material and collect in closed container for disposal using non-sparking tools. Ventilate area and wash spill sites after material pickup is complete, rinse with water. All clean up should be carried out in accordance with federal, state, and local regulations. If required proper authorities should be notified.

**SECTION 7. STORAGE AND HANDLING PRECAUTIONS**

---

**STORAGE:** Store in tightly closed container in a cool environment away from direct sunlight.

**HANDLING:** Use only under yellow light.  
Keep away from heat, sparks, and flames.  
Use only with mechanical exhaust.  
Do not contact with skin, eyes, and clothing.

**MATERIAL SAFETY DATA SHEET**PAGE 3  
12 December 2001CHEMICAL NAME: Organic Resin Solution  
TRADE NAME: SU-8 Resist Series

PRODUCT #: See Table 1 – Section 9

Severe eye irritant.  
Avoid prolonged or repeated exposure.  
Wear heavy rubber gloves.  
Wash with soap and water after handling.  
Have safety shower and eye wash available.

**SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION-----**

RESPIRATORY PROTECTION: In case of spills, use of self-contained breathing apparatus (SCBA) is recommended.  
VENTILATION: Local or general mechanical ventilation is required.  
SKIN PROTECTION: Rubber gloves are recommended.  
EYE PROTECTION: Safety goggles are highly recommended.

**SECTION 9. PHYSICAL AND CHEMICAL DATA-----**

APPEARANCE: Pale yellow to clear  
ODOR: Slightly sweet  
BOILING POINT: 204 °C (400 °F)  
SPECIFIC GRAVITY: See Table 1 below  
VAPOR PRESSURE: 2 mm @ 20 °C (68 °F)  
H<sub>2</sub>O SOLUBILITY: See Table 1 below  
% VOLATILES: See Table 1 below  
EVAPORATION RATE: 1 (BuAc=1)  
FLASH POINT: 98 °C (209 °F) TCC  
AUTOIGNITION TEMP: 437 °C (820 °F)  
EXPLOSION LIMITS: 3.6 lower  
16 upper

**Table 1**

Name	Product#	Specific Gravity (g/ml)	Volatiles (% by wt.)	H <sub>2</sub> O Solubility (% by wt)	VOC (g/L)	SbF <sub>6</sub> Salt (% by wt)	Sb (% by wt)
SU8-2	Y131240	1.123	60.5	60.5	680	1.9	<1.0%
SU8-5	Y131252	1.164	45-50	45-50	560	2.5	<1.0%
SU8-10	Y131259	1.187	35-40	35-40	490	2.8	<1.0%
SU8-25	Y131263	1.200	35-40	35-40	440	3.0	<1.0%
SU8-50	Y131269	1.219	30-35	30-35	380	3.3	<1.0%
SU8-100	Y131273	1.233	20-30	20-30	330	3.5	<1.0%
SU8-250	Y131274	1.236	20-30	20-30	320	2.2	<1.0%
SU8-500+	Y131275	1.237	20-30	20-30	310	1.5	<1.0%

**MATERIAL SAFETY DATA SHEET**

PAGE 4  
12 December 2001

CHEMICAL NAME: Organic Resin Solution  
TRADE NAME: SU-8 Resist Series

PRODUCT #: See Table 1 – Section 9

-----

**SECTION 10. REACTIVITY DATA** -----  
-----

STABILITY: Stable  
INCOMPATIBILITY: Strong Oxidizing Agents, Strong Bases, Strong Acids  
HAZARDOUS POLYMERIZATION: Will not occur  
HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Carbon Monoxide, Aldehydes, Acids, Hydrogen Fluoride Gas.

**SECTION 11. TOXICITY HAZARDS**-----  
-----

**Gamma Butyrolactone**

In animal studies, due to the rate of dermal absorption of GBL, dermal toxicity is assumed to be essential equal to oral toxicity. In humans, oral ingestion of solutions containing high concentrations of GBL has caused reversible coma.

**Mixed Triarylsulfonium/Hexafluoroantimonate Salt/Propylene Carbonate**

This material was mutagenic in the Ames bacterial assay. It is inactive, however, in the in vivo mouse micronucleus test.

**SECTION 12. ECOLOGICAL DATA**-----  
-----

No data available at this time.

**SECTION 13. DISPOSAL CONSIDERATIONS**-----  
-----

Burn in an EPA-licensed chemical incinerator equipped with an afterburner and scrubber at an approved waste disposal facility. Observe all federal, state, and local environmental regulations.

CHEMICAL NAME: Organic Resin Solution  
TRADE NAME: SU-8 Resist Series

PRODUCT #: See Table 1 – Section 9

-----  
**SECTION 14. TRANSPORTATION INFORMATION**-----  
---

HAZARD CLASSIFICATION: Not Regulated  
SHIPPING NAME: Not Regulated  
UN NUMBER: Not Regulated  
PACKING GROUP: Not Regulated

-----  
**SECTION 15. REGULATORY INFORMATION**-----  
---

HAZARDOUS LISTINGS: All ingredients appear on the TSCA Inventory of  
Chemical Substances, EINECS, and the Japan  
Hazardous Chemical Listing.  
SARA Title III: This product IS NOT subject to SARA Title III, Section  
313 Reporting Requirements.  
Calif. SCAQMD Rule 443.1 VOC's: See Table 1 – Section 9

-----  
**SECTION 16. ADDITIONAL PRECAUTIONS AND COMMENTS**-----  
=

To the best of our knowledge, the above information is believed to be accurate but does not claim to be all-inclusive and is intended to be used only as a guide. The supplier makes no warranty of any kind, expressed or implied, concerning the use of this product and shall not be held liable for any damage resulting from handling or from contact with the above product. User assumes all risks incident to its use.